



## Ultra-ADA Pads Surface Mount (Retrofit) Model

### S P E C I F I C A T I O N S

| <b>General Information</b>  |                         |  |
|---|-------------------------|--|
| Material: Flexible Urethane   |                         |  |
| Sizes: 2' x 2', 2' x 3', 2' x 4', 2' x 5'   |                         |  |
| Precautions:<br>Product must be installed on dry surfaces<br>Product should be installed at temperatures between 40° F (4° C) to 100° F (38° C) |                         |  |
| Recommended Maintenance: Power washing approximately every six months   |                         |  |
| <b>Test</b>   | <b>ASTM Test Method</b> | <b>Value</b>   |
| Weatherometer Exposure  | G155-05a                | 200 hours – no cracks  |
| Corrosion Resistance  | B117-07                 | 200 hours – no corrosion or change in appearance   |
| Tensile   | D412-06a                | Median 2069<br>Elongation at break, 400%   |
| Abrasion Resistance   | D4060-07                | Ave Wt Loss, L 143.7 mg<br>Ave Wear Index, I 144   |
| Abrasion Resistance   | C-501                   | 1000 Cycles WI 292<br>2000 Cycles WI 336   |
| "Slip Test"   | C-1028-07               | Static Coefficient of Friction – Dry = 1.16<br>Static Coefficient of Friction – Wet = 1.01 |