

Unique, “Living Hinge” Design Allows Hands-Free Drive In/Drive Out — No Need To Manually Raise Or Lower The Endwalls



Part# 8506



- Entry and exit walls are supported every 12” with a patented “living hinge”.
- Once a vehicle has entered or exited, the walls automatically spring back to their vertical position.
- Both long sidewalls are held upright by PVC sidewall assemblies. Simply swivel the feet to lower the sidewalls for storage or transport to another location.
- **Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175.**



Two-way “living hinge” design allows convenient, hands-free drive in/drive out.



PVC sidewall assemblies can be easily lowered and raised.

Drive-in/drive-out endwalls teamed up with collapsible sidewalls offer the ultimate combination — “Hands Free” convenience and an affordable design!

Custom sizes available.

ULTRA-CONTAINMENT BERMS, ULTIMATE MODEL

Part #	Dimensions	Weight	Containment Capacity
8505	12' x 60' x 1' (3.7 m x 18.3 m x .3 m)	309 lbs. (140 kg)	5,385 gallons (20,382 L)
8506	15' x 50' x 1' (4.6 m x 15.2 m x .3 m)	326 lbs. (148 kg)	5,610 gallons (21,234 L)
8507	15' x 66' x 1' (4.6 m x 20.1 m x .3 m)	405 lbs. (184 kg)	7,405 gallons (28,028 L)

Material of Construction: Copolymer 2000™, an ethylene copolymer, is standard. Copolymer 3000™, XR5, polyurethane and other materials are also available on a custom basis.
Options: Ground Tarps, Track Belts, Self Bailer, see page 31.

U.S. Patent No. 5,924,461