

UltraGutter Guard Plus®

Guard High-Flow Curb Inlets From Silt, Sediment And Other Contaminants



Part# 9151

Available in many standard and custom sizes (allow 12" overlap on each side of inlet).

- Designed for curb inlets with high-flow volumes.
- Unique, multi-dimensional outer filter combined with rigid inner frame maintains a low profile to prevent damage from vehicular traffic.
- Modular, 3-foot inner frames allow for compact transport and storage.
- Counterweight inserts into inlet to keep unit upright and secure — see inset photo (7 lb. weight available).*
- Tie-back straps on either end of unit can be used with sod pin or stake for additional anchoring.
- Can be easily cleaned and reused.
- **Helps comply with NPDES, 40 CFR 122.26 (1999).**

ULTRA-GUTTER GUARD PLUS		
Part# 9151	Dimensions: 6' L x 6" H (1,829 mm x 152 mm)	Weight: 10 lbs. (4.5 kg)
Part# 9158	Dimensions: 9' L x 6" H (2,743 mm x 152 mm)	Weight: 13 lbs. (6 kg)
Part# 9154	Dimensions: 12' L x 6" H (3,658 mm x 152 mm)	Weight: 16 lbs. (7 kg)
Part# 9159	Dimensions: 15' L x 6" H (4,572 mm x 152 mm)	Weight: 20 lbs. (9 kg)
Part# 9148	Counterweight Dimensions: 14" L x 1 1/2" dia. (356 mm x 38 mm dia.)	Weight: 7 lbs. (3 kg)

*One weight required for Part# 9151. Two required for all other sizes.

UltraGutter Guard®

Keep Sediment And Other Debris Out Of Curb Inlets

- Made of 100% recycled materials.
- Can be reused — simply remove, clean and store properly until needed again.
- Built-in overflow ports allow water to pass through during major rainfall events.
- **Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.**



ULTRA-GUTTER GUARD	
Part#	Dimensions
9320	9" dia. x 8' L (229 mm dia. x 2,438 mm L)
9321	9" dia. x 10' L (229 mm dia. x 3,048 mm L)
9322	9" dia. x 12' L (229 mm dia. x 3,658 mm L)

- Quick and easy installation — no stakes, weights or hardware required. Simply place in front of curb inlet assuring at least a 12" overlap on each side.