

Ultra® Containment Berms

Economy Model

Economical Design Offers Cost Savings And Secure Containment

- L-shaped aluminum brackets provide sturdy sidewall support
- Easy assembly — Brackets are quickly and easily inserted into sleeves spaced around perimeter of Berm
- No frames, components or excess material outside of sidewalls — excellent for use inside storage sheds and other buildings or structures where floor space is a premium.
- **Meets SPCC and EPA Container Storage Regulations 40 CFR 264.175.**

Compact shipping and storage — with frames removed, Berm requires very little space (10' x 10' unit shown).



ULTRA-CONTAINMENT BERMS, ECONOMY MODEL

Part#	Dimensions	Weight	Containment Capacity
8250	4' x 6' x 1' (1.2 m x 1.8 m x .3 m)	21 lbs. (9.5 kg)	179 gallons (678 L)
8251	6' x 6' x 1' (1.8 m x 1.8 m x .3 m)	26 lbs. (12 kg)	269 gallons (1,018 L)
8252	10' x 10' x 1' (3.0 m x 3.0 m x .3 m)	52 lbs. (23.5 kg)	748 gallons (2,831 L)
8253	12' x 60' x 1' (3.7 m x 18.3 m x .3 m)	268 lbs. (121.5 kg)	5,385 gallons (20,382 L)
8254	15' x 50' x 1' (4.6 m x 15.2 m x .3 m)	259 lbs. (117.5 kg)	5,610 gallons (21,234 L)
8255	15' x 66' x 1' (4.6 m x 20.1 m x .3 m)	334 lbs. (151.5 kg)	7,405 gallons (28,028 L)

Material of Construction: Copolymer 2000™ an ethylene copolymer, is standard. Copolymer 3000™, XR5, polyurethane and other materials are also available on a custom basis.
Options: Ground Tarps, Track Belts, Pull Over Covers. Self Bailer, see page 31.

Ultra® Drum Lifter



ULTRA-DRUM LIFTER

Part# 0409
Load Capacity: 1,000 lbs. (455 kg)
Weight: 20 lbs. (9 kg)

- Securely grips 55 gallon steel drums when loading and unloading salvage drums.
- Rugged, all-steel construction.

Ultra® Drum Tipper



ULTRA-DRUM TIPPER

Part# 0851
Dimensions: 11 1/2" x 11 1/2" (292 mm x 292 mm)
Weight: 3 lbs. (1.5 kg)



- Residual liquids flow to one side of drum for efficient pumping — valuable chemicals can be used, not wasted.
- Durable, all polyethylene construction — designed for use with 30 gallon or 55 gallon drums.