



## Reduce Water Velocity In Gullies, Ditches, And Construction Sites

Ultra-GullyGuard is a permeable device that is installed across ditches and gullies where runoff and water is channeled. The device checks the water flow and traps sediment and/or oil depending on the model used.



- **Keep sediment and oils from contaminating downstream aquatic environments.**
- **Helps minimize erosion.**
- **Helps comply with NPDES and SPCC.**

ULTRA-GULLYGUARD		
Part#: 9710-SED	Sediment Only Model, 7" dia. x 4' L	Wt: 20 lbs.
Part#: 9711-SED	Sediment Only Model, 7" dia. x 7' L	Wt: 25 lbs.
Part#: 9710-O/S	Oil/Sediment Model, 7" dia. x 4' L	Wt: 21 lbs. Absorbs up to .9 gal. of oil/unit
Part#: 9711-O/S	Oil/Sediment Model, 7" dia. x 7' L	Wt: 27 lbs. Absorbs up to 1.5 gal. of oil/unit
Use optional connector (Part# 9713) for applications that require longer GullyGuards. Other stock sizes and custom sizes available. Replacement Oil-Only Absorbent Socks Available for Oil/Sediment Model Ultra-GullyGuards.		



## Prevent Erosion And Keep Sediment Out Of Storm Drains And Waterways

Ultra-SiltFence is conveniently shipped in pre-assembled 100-foot lengths. Includes 2" square, sharpened, hard-wood stakes with 3 staples to hold the silt-controlling, polypropylene material firmly in place.



- **Contractor-grade material in heights of 24" and 36".**
- **Easy and economical way to meet erosion and sediment control at construction sites.**
- **DOT-grade material available.**
- **Helps comply with NPDES and SPCC.**

ULTRA-SILTFENCE		
Part#: 9715-WS	Ultra-SiltFence 24" H x 100' L	Weight: 30 lbs.
Part#: 9716-WS	Ultra-SiltFence 36" H x 100' L	Weight: 40 lbs.



## Temporary Berm Seals Off Spills From The Environment, Nearby Drains And Doorways

- **Unique, urethane material "weeps" into small cracks and crevices to seal off liquid flow.**
- **SpillBerm is non-absorbing and is easily cleaned for repeated use.**
- **Applications include: Spill Response/Temporary Secondary Containment/Sealing Off of Doorways During Washdown Operations.**
- **Helps comply with NPDES and SPCC.**

U.S. Patent No. 5,236,281.

ULTRA-SPILLBERM	ULTRA-SPILLBERM PLUS
<b>Orange: Part# 2100    Black: Part# 2050</b>	<b>Part# 2054</b>
Dimensions: 10' x 4" x 2 1/4"	Dimensions: 5' x 4" x 4 1/2"
Weight: 31 lbs. per unit	Weight: 16 lbs. per unit
Material: Non-absorbing polyurethane	Material: Non-absorbing polyurethane
Optional connectors (Part# 2101) used to connect 10' sections	Built-in connectors allow multiple units to be quickly and easily connected
Optional corners (Part# 2102) are used with Connectors to make 90° Corners	



**NEW!**



**Did you know? — The new Spill Prevention Control and Countermeasure Act (SPCC) will require over 419,000 industrial facilities to develop SPCC plans that will include spill containment products.**