



## Control The Flow Of Sediment And Oil Out Of Headwall And Other Types Of Pipes

- Use in pond applications where vertical pipes extend above the water surface, and preventing sediment in-flow during high-water events is required.
- Several standard and custom sizes available.
- **Helps comply with NPDES, 40 CFR 122.26 (1999).**



ULTRA-PIPESOCK	
Part# 9705-O/S	Oil/Sediment Model, for 8" dia. Pipe, 60" L
Part# 9707-O/S	Oil/Sediment Model, for 16" dia. Pipe, 60" L
Other stock sizes and custom sizes available.	

U.S. Patent No. 6,632,501



## Triangular Silt Dike™ Barrier Systems Help Contain Eroded Soils

- Designed as an effective and economical alternative to straw bales, silt fence and rock check dams.
- Patented design provides effective erosion and sediment control.
- Aprons on either side of Dike prevent erosion and failure of the structure. Optional, U-shaped wire staples help secure unit in place and conform to rough terrain.
- Lightweight and durable construction — installs in minutes.
- Multiple units can be installed side-by-side for larger areas.
- Other uses include: ditch check dams, diversion dikes, drop inlet protection, continuous barrier, temporary ditch liner and stream and pond protection.



ULTRA-SILT DIKE	
Part# 9712	
Dimensions: 84" L x 67" W x 10.5" H	
Weight: 8 lbs.	
Options: U-Shaped Staples (Part# 9714)	



## Minimize Erosion and Sediment Runoff

- Use instead of silt fence to reduce erosion at construction sites — stops sediment and other debris from entering retentions ponds, lakes and other water bodies.
- Environmentally-friendly — units can be left in place to eventually "mulch in" with surrounding environment.
- Less intrusive and conspicuous than silt fence — perfect for use in ongoing residential and commercial construction projects.
- Installation is quick and easy — simply dig shallow trench and stake in place.
- Can be used as check dams to reduce water velocity.
- Requires no maintenance or upkeep.
- **Helps comply with NPDES, 40 CFR 122.26 (1999).**



Minimize erosion on slopes and inclines — perfect for construction sites, fire burn rehabilitation, timber harvest erosion control and revegetation projects.

ULTRA-STORMWATTLES	
Part #	Dimensions
9740	9" dia. x 10' L
9741	9" dia. x 25' L
9742	12" dia. x 10' L
9743	12" dia. x 25' L