



**ULTRATECH**  
INTERNATIONAL, INC

## Ultra-Gutter Guard Plus®

### Product Data Sheet

Part#	9151, 9154, 9158, 9159
Dimensions In. (mm)	9151: 6' L x 6" H (1,829 x 152 mm) 9158: 9' L x 6" H (2,742 x 152 mm) 9154: 12' L x 6" H (3,658 x 152 mm) 9159: 15' L x 6" H (4,572 x 152 mm)
Weight lb. (kg)	9151: 10.0 lb. (4.5 kg) 9158: 13.0 lb. (6.0 kg) 9154: 16.0 lb. (7.0 kg) 9159: 20.0 lb. (9.0 kg)
Color	Yellow
Construction	Polypropylene
Compliance	Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.



# **Ultra-Gutter Guard Plus™ General Specification**

## **For Curb Inlet Storm Drains**

### **1.0 Description:**

1.1 This work shall consist of furnishing, placing, maintaining and removing the Gutter Guard Plus sediment control device as directed by the engineer and as shown on the contract drawings

### **2.0 Material:**

#### **2.1 Gutter Guard Plus**

The Ultra-Gutter Guard Plus will be manufactured to 3' molds in 6', 9', 12', 15' and 18' lengths and a minimum of twenty-four (24) inches longer than the curb inlet opening. This will allow for sufficient length to cover the inlet with twelve (12) inches beyond the inlet on both ends.

### **3.0 Construction Sequence:**

#### **3.1 ttGeneral**

3.1.1. Install the Gutter Guard Plus in front of the curb inlet opening. Drop 7lb weight sock into inlet opening, secure tie back straps, if applicable. Each end of the Gutter Guard Plus should overlap the curb inlet approximately 12".

3.1.2 The Gutter Guard Plus should be cleaned if a visual inspection shows sediment and debris build up around the Gutter Guard Plus.

3.1.3 To remove the Gutter Guard Plus, lift out of curb opening with provided carrying handle.

3.1.4 Clean as needed. Store out of direct sunlight.